

BENZOXE

Benzoyl Peroxide Wet (75%)

BPO is used for resins, which are no hindrance of water content, as polymerization catalyst, and generally used for suspension polymerization of polystyrene monomer as well as emulsion polymerization of methyl methacrylate monomer.

Benzoxe is a Surfactant free product.

Specifications and Properties:

Appearance :	Crystallized powder, white color, odorless
Free acid :	0.5% max
Chlorine :	0.10% max in acetone complete solution
Active Oxygen :	4.86 – 5.05%
Purity :	73.5 – 76.5%
Specific Gravity :	1.33 (at 25°C)
Solubility insoluble :	Water
Slightly Soluble :	Alcohol, Styrene
Soluble :	Acetone, Methyl ethyl ketone, Toluene

Packaging :

Supply Container (type)	Polyethylene bag, carton box
Supply Container (content)	Double polybag @ 10Kg = 20Kg/carton box

PT. KAWAGUCHI KIMIA INDONESIA

Office : Jl. Let Jend S. Parman Kav 12 Lt.10 No.1009, Jakarta Barat 11480 - Indonesia
Phone : (62-21) 5305901 Fax : (62-21) 5305908
Factory : Jl. Raya Serang KM. 12,5 Cikupa – Tangerang 15170